

TH6

6-Channel High-definition Hybrid DVR

The Future of High-definition Surveillance

This high-definition (HD) digital video recorder (DVR) records up to six high-definition camera views, while offering the flexibility to support existing standard resolution (analog) cameras. The TH6 supports up to six cameras in total – any combination of your choice of HD or Standard resolution. HYBRID technology allows you to upgrade to HD at your own pace while preserving your initial camera investment.



Ideal for: Interior & Exterior School Bus, Para-transit and Shuttle Bus Security

Full High-definition Surveillance

Record up to six high-definition camera views with audio at up to 30 FPS on all channels simultaneously.

Hybrid Technology: Your Choice – Analog or HD

Support your existing cameras while upgrading to HD with your choice of recording resolution from D1 to 1080p.

Video Loss Protection

Supercaps technology ensures your DVR continues to record even after a sudden power loss during an accident.

Redundant Recording

Supports recording of secondary video stream to optional back-up SD card for added reliability.

Compatible with any Seon analog and new high-definition dome and wedge Cameras:



HD3Q Interior Dome



HD3U Interior Camera



HD3W Outdoor Wedge

Accessories:



Event/Diagnostic Button



Hard Drive Reader



GPS



G-Force Sensor

Optional Add-ons:



Wi-Fi auto-download & Video management



Live GPS Tracking



Live Video Streaming

TH6

6-Channel High-definition Hybrid DVR



Video	
Recording Channels	6 channels (HD or Std Res), 6 audio channels
Video Resolution	Total of 6 CH, configurable per CH: 1280x720 (720p) up to 6 CH main stream 1920 x1080 (1080p) up to 6 CH main stream 720x480 (D1) up to 6 CH main stream CIF all CH for second stream recording
Recording Rate Main Stream	30 FPS (180 FPS aggregate) at D1/720p; 15 FPS (90 FPS aggregate) at 1080p
Recording Rate Second Stream	1 - 5 FPS independent of the main stream
Quality Settings	Adjustable, 4 levels
Auto Overwrite	Selectable On/Off
Display Modes	Single camera, six-up on the DVR video out Single camera, six-up on the vMax Web
Playback Rate	Frame advance, FFD and REV playback up to 32x
Search Function	Segment, alarm, date/time, event
User Interface	OSD with mouse, vMax Web (web browser), vMax® View software suite
Delay On/Off	Record Delay on ≤1 hr Record Delay off ≤1 hr Power Delay off ≤4 hr
On-Screen Display	Main title, time & date, record status
Dual Streaming	Capable of sending low-bandwidth video images live over an optional broadband (cellular) network
Storage	
Primary	Up to 2 TB (HDD)
Secondary	Up to 512GB (SD Card)
Input/Output	
Network Interface	3-port Ethernet switch (TCP/IP)
Wiring Harness	20' (6 m) harness for power
Panic Alarm Input	20' (6 m) harness with panic button

Smart Features	
Smart-Temp™	Ensures the DVR stays at its optimal operational temperature
Smart-Start™	Safeguards the DVR against electrical spikes with vehicle start-up voltage protection
Inertia Sensor	3 axis internal G-sensor
Electrical	
Voltage Range	8 to 32 VDC
Transient Protection	600 W for power input, 400 W per signal input
Configuration Backup	Time & programmed info (retained up to 10 years)
Mechanical/General	
Dimensions (H x W x D)	2.5 x 7 x 9.5 in (64 x 188 x 241 mm)
DVR Weight	5.3 lbs (2.4 kg) with lock-box
Environmental	
Operating Temperature	-30 to 50°C (-22 to 122°F)
Approvals	
Emissions	FCC Part 15, Class B
Vibration	Vibration Tested against SAE-1455 and MIL-STD 810F
Specifications – Plus System	
Signals	5 external signal inputs + 5 internal signals
Alarms	4 internal alarms to connect to signals or internal triggers, + 1 external alarm
Event/Diagnostic Button	An indicator panel that marks events for quick searches and displays DVR status
GPS Ready	Records vehicle speed and location with optional GPS receiver; enables synchronized mapping when used with vMax® software
Geo-fencing	Uses GPS technology to set a geographical boundary for a vehicle; receive an alert if it deviates
SuperCaps	Protects against video loss in case of sudden power disruption such as during an accident

1021-TH6-Spec-Sheet-SS-ST-112719

Copyright ©2019 Safe Fleet and its subsidiaries. All rights reserved. No part of this publication may be reproduced by any means without written permission from Safe Fleet. The information in this publication is believed to be accurate. However, Safe Fleet does not make any representation or warranty to that effect and does not assume responsibility for any consequences resulting from use of such information. Revisions or new editions of the publication may be issued (or not issued) in our discretion to incorporate such changes.

SEON

1.877.630.7366
safefleet.net

SAFE FLEET
Driving Safety Forward™